

# On- and Off Dynamics and Respiration Rate Enhance the Accuracy of Heart Rate Based VO<sub>2</sub> Estimation

A. Pulkkinen, J. Kettunen, K. Martinmäki, S. Saalasti, H.K. Rusko, FACSM  
 KIHU-Research Institute for Olympic Sports, Jyväskylä, Finland

ON- AND OFF DYNAMICS AND RESPIRATION ENHANCE THE ACCURACY OF HEART RATE BASED VO<sub>2</sub> ESTIMATION  
 A. Pulkkinen, J. Kettunen, K. Martinmäki, S. Saalasti, H.K. Rusko, FACSM  
 KIHU-Research Institute for Olympic Sports, Jyväskylä, Finland

Current heart rate (HR) based calculations use linear steady state based function to calculate VO<sub>2</sub> from HR. HR to VO<sub>2</sub> relationship changes during variations in exercise intensity and non-exercise related physiological processes affecting HR especially at low intensity. **PURPOSE:** To examine whether addition of On- and Off- VO<sub>2</sub>-dynamics (VO<sub>2HR-ON/OFF</sub>) and respiration rate (VO<sub>2HR+Resp</sub>) or both (VO<sub>2HR+Resp+ON/OFF</sub>) increase the accuracy of HR based VO<sub>2</sub> estimation (VO<sub>2HR</sub>). **METHODS:** Beat-by-beat HR and breath-by-breath VO<sub>2</sub> data from 16 male and 16 female healthy untrained adults (age of 38±9 years, weight 70±11 kg, height 172±8 cm and VO<sub>2max</sub> 44±9 ml/kg·min<sup>-1</sup>) were collected 5 minutes prior to and 15 minutes after 10-min exercises at 40% and 70% VO<sub>2max</sub> and maximal stepwise test on bicycle ergometer. Two 50 min series of simulated low intensity real life tasks (RLT, mean HR 101±8 and 105±9 bpm) were also carried out. On- and Off- VO<sub>2</sub> changes were used to model VO<sub>2</sub> dynamics. Four neural network models were constructed using 3% from the data in the learning process: VO<sub>2HR</sub>, VO<sub>2HR+Resp</sub>, VO<sub>2HR-ON/OFF</sub>, VO<sub>2HR+Resp+ON/OFF</sub>. The whole dataset was used to evaluate the accuracy of the methods using mean absolute error (MAE) between estimated and measured VO<sub>2</sub>. **RESULTS:** Accuracy was enhanced (p<.001) in all exercise conditions and during RLTs when ON/OFF-response information was included. Across all subjects and conditions MAE of VO<sub>2HR</sub> 3.7 ml/kg·min<sup>-1</sup> was reduced to 3.3, 2.3 and 1.9 ml/kg·min<sup>-1</sup> improving the accuracy by 11%, 38% and 48% using VO<sub>2HR+Resp</sub>, VO<sub>2HR-ON/OFF</sub>, VO<sub>2HR+Resp+ON/OFF</sub> methods, respectively. During maximal exercise test MAE of VO<sub>2HR</sub> 4.9 ml/kg·min<sup>-1</sup> was reduced to 4.4, 1.8 and 1.3 ml/kg·min<sup>-1</sup> improving the accuracy by 6.1%, 60.9% and 70.7% using VO<sub>2HR+Resp</sub>, VO<sub>2HR-ON/OFF</sub>, VO<sub>2HR+Resp+ON/OFF</sub> methods, respectively. **CONCLUSIONS:** Both On- and Off- dynamics and respiration were able to enhance the accuracy of VO<sub>2</sub> estimation compared with VO<sub>2HR</sub> from maximal to varying low intensity exercise. The greatest and the most consistent improvements were due to On- and Off-dynamics.

## INTRODUCTION

Heart rate (HR) recording is the most commonly used method to estimate oxygen (VO<sub>2</sub>) and energy consumption in field. HR to VO<sub>2</sub> relationship is unambiguous during steady state at moderate intensity but may be considerably different especially during dynamically changing exercise intensity and due to psychological factors affecting HR at low intensity exercise.

The purpose of this study was to examine whether information on On- and Off- dynamics and respiration rate can increase the accuracy of HR based VO<sub>2</sub> estimation during dynamic changes in exercise intensity and during low intensity exercise.

## METHODS

Subjects were 32 healthy adults (16 males, 16 females), age 38±9 years (mean±SD), weight 69.6±10.8 kg, height 171.6±8.5 cm and VO<sub>2max</sub> 44.0±8.8 ml/kg·min<sup>-1</sup>. Submaximal steady state and maximal incremental bicycle ergometer (Ergoline, Bitz, Germany) exercises and real life tasks (RLT) were carried out during two different days separated by 1-2 weeks (Figure 1). RLT's included simulated low intensity household, recreational and occupational tasks, such as: sweeping the floor; walking; walking in stairs; carrying load; pushing shopping wheels; lifting and moving light weights; computer tasks and free standing and sitting.

HR-data was collected with rr-recorder (Polar Electro Oy, Kempele, Finland). During bicycle ergometer exercises VO<sub>2</sub> data was collected breath-by-breath using Vmax (Sensor Medics, California, Palo Alto, USA) and during RLT's using portable Cosmed K4 analyzer (S.r.l, Italy). Specialized heartbeat analysis software (Firstbeat Technologies Oy., Jyväskylä, Finland) was used to perform heartbeat analysis.




Figure 1. The procedure

Randomly selected data sample representing three percent from the total dataset was used to construct four different neural network (NN) models to estimate second-by-second VO<sub>2</sub>:

- (1) from HR only (VO<sub>2HR</sub>),
- (2) from HR and respiration rate (VO<sub>2HR+Resp</sub>),
- (3) from HR, respiration rate and On- and Off- VO<sub>2</sub> dynamics (VO<sub>2HR+Resp+ON/OFF</sub>) and
- (4) from HR and information on On- and Off- VO<sub>2</sub> dynamics (VO<sub>2HR-ON/OFF</sub>).

VO<sub>2</sub>, HR and Resp used in the NN modeling were scaled according to the respective individual measured maximum.

The accuracy of the estimates was evaluated using whole dataset (100%) by mean absolute errors (MAE) and error in percent (%-error) between the measured and estimated values. Paired t-test was used to examine whether accuracy was improved using VO<sub>2HR+Resp</sub>, VO<sub>2HR-ON/OFF</sub> or VO<sub>2HR+Resp+ON/OFF</sub> -method compared with the VO<sub>2HR</sub> -method.

## RESULTS

### VO<sub>2</sub> & HR kinetics

HR to VO<sub>2</sub> relationship had different patterns during On- and Off-responses in 40%, 70% and VO<sub>2max</sub> test conditions (Figure 2). HR and VO<sub>2</sub> drifted to higher level during 70% bicycle exercise (Table 1).

### VO<sub>2</sub> estimation

Including all bicycle and real life task conditions, MAE between the measured and estimated VO<sub>2</sub> was 3.7, 3.3, 2.3 and 1.9 ml/kg/min using VO<sub>2HR</sub>, VO<sub>2HR+Resp</sub>, VO<sub>2HR-ON/OFF</sub> and VO<sub>2HR+Resp+ON/OFF</sub> -method, respectively. Compared with VO<sub>2HR</sub>, error was reduced by 11%, 38% and 48% with VO<sub>2HR+Resp</sub>, VO<sub>2HR-ON/OFF</sub> and VO<sub>2HR+Resp+ON/OFF</sub>, respectively. (Figure 3.) In each of the different bicycle and real life task conditions, VO<sub>2HR-ON/OFF</sub> and VO<sub>2HR+Resp+ON/OFF</sub> increased the accuracy of VO<sub>2</sub> estimation highly significantly, whereas VO<sub>2HR+Resp</sub> mostly only during maximal test conditions and RLT<sub>2</sub> (Table 2).






Figure 2. On- and off- responses of VO<sub>2</sub> and HR during bicycle ergometer exercises.





Figure 3. MAE (TOP) and %-error (BOTTOM) of VO<sub>2</sub> estimation methods across all intensities.

Table 1. HR (bpm) and VO<sub>2</sub> (ml/kg·min<sup>-1</sup>) drift bicycle exercises.

Time	40% (n=23)		70% (n=22)	
	VO <sub>2</sub>	HR	VO <sub>2</sub>	HR
3 <sup>rd</sup> min	17.0±3.7	104±8	28.6±6.0	135±9
9 <sup>th</sup> min	17.1±3.7	106±9	29.9±6.4***	144±10***

\*\*\* p<.001 different from 3<sup>rd</sup> min.

Table 2. MAE and %-increase in accuracy compared to VO<sub>2HR</sub>.

Exercise condition	VO <sub>2</sub> (ml/kg/min)	MAE VO <sub>2</sub> (ml/kg·min <sup>-1</sup> )			% increase in accuracy		
		VO <sub>2HR</sub>	VO <sub>2HR+Resp</sub>	VO <sub>2HR-ON/OFF</sub>	VO <sub>2HR+Resp</sub>	VO <sub>2HR-ON/OFF</sub>	VO <sub>2HR+Resp+ON/OFF</sub>
40% n=23	ON	14.9±3.0	3.7±1.3	3.8±1.7	2.7±1.1***	2.1±1.0***	-2±21
	OFF	3.4±0.8	2.6±1.4	2.3±0.8	2.3±1.2***	2.0±0.6**	1±33
	SS	17.0±3.6	3.5±1.6	3.5±1.8	1.3±0.7***	1.4±1.0***	-4±43
70% n=22	ON	23.5±4.8	3.8±1.6	3.4±1.5	2.0±0.7**	1.5±0.4***	5±30
	OFF	4.8±0.9	4.5±2.3	3.9±1.8	2.7±1.1***	2.0±0.8***	7±28
	SS	29.8±6.0	3.3±2.0	2.8±1.6	0.9±1.2***	0.8±0.6***	6±38
Max n=28	ON	27.0±4.5	3.1±1.1	2.6±0.9***	1.3±0.4***	0.9±0.2***	13±13
	OFF	9.0±2.3	9.0±3.8	8.3±2.8*	2.6±1.0***	1.7±0.5***	2±24
	RLT1 n=19	11.6±1.4	3.7±0.8	3.5±0.7	2.3±0.7***	2.2±0.6***	6±13
RLT2 n=25	15.5±2.3	4.2±1.2	3.7±1.2**	2.9±0.9***	2.6±0.8***	12±18	
						30±9	38±11

\* p<.05, \*\* p<.01, \*\*\* p<.001 more accurate than VO<sub>2HR</sub>.

## DISCUSSION

The results confirmed that On- and Off-dynamics of HR and VO<sub>2</sub> are different during changes in exercise intensity and should be taken into account when estimating VO<sub>2</sub> in field.

The results indicate that VO<sub>2HR-ON/OFF</sub> and VO<sub>2HR+Resp+ON/OFF</sub> were able to correct the error in VO<sub>2HR</sub> estimate due to different VO<sub>2</sub> to HR patterns during On- and Off-responses in bicycle exercise conditions (Figure 2). Accuracy was also significantly enhanced during steady-state bicycle exercise, possibly due to the ability of On- and Off- information to correct different proportions of VO<sub>2</sub> and HR drift (Table 1) and natural changes in power, HR and VO<sub>2</sub> during steady state.

Information on On- and Off- dynamics and respiration rate also differentiated between dynamically changing low-intensity exercise and psycho-physiologically related HR responses, since VO<sub>2</sub> estimation was enhanced during low intensity exercise simulating daily activities (RLT).

Methods presented reduce very significantly the error in VO<sub>2</sub> estimation, and can provide a new level of accuracy for field applications, since On- and Off- dynamics and respiration rate can be estimated reliably from RR-interval data only (e.g. Saalasti, S. 2003, Neural Networks for Heart Rate Time Series Analysis. Academic Dissertation, University of Jyväskylä, Jyväskylä, Finland).

## CONCLUSIONS

1. On- and Off- dynamics of VO<sub>2</sub> and HR are different.
2. HR based VO<sub>2</sub> estimation can be enhanced using information on On- and Off- dynamics during: a) dynamically changing exercise intensity, b) steady-state exercise and c) low intensity exercise simulating daily activities.
3. On- and Off-response dynamics and respiration rate can be derived reliably using beat-to-beat RR-interval data only allowing more accurate VO<sub>2</sub> estimation for field applications.

## ACKNOWLEDGEMENTS

This study was supported by Suunto Oy and Firstbeat Technologies Oy.